

GP-10(60000) SILICONE FLUID

Genesee Polymers' *GP-10(60000) SILICONE FLUID* is a dimethyl polysiloxane that is an inert, clear and colorless liquid with a viscosity of 60,000 cPs at 25° C. Chemical inertness, non-corrosivity, thermal stability, low levels of toxicity and high lubricity make GP-10(60000) the product of choice for many diverse applications.

GP-10(60000) SILICONE FLUID is among the most versatile, cost-effective material for release agent, lubricant and polish applications.

TYPICAL PROPERTIES	
Appearance	Clear, Colorless Liquid
Weight/Gallon	8.0 lbs
Viscosity	60,000 cPs
Flash Point (P.M.C.C.)	>300º F
Refractive Index	1.4081
% Solids (1 hr. @ 105º C)	>98%

INNOVATIVE POLYMER TECHNOLOGY

Version: 3.0

APPLICATIONS

Car Polishes

Release Agents

Textile Lubricant

Vinyl Fabric Protectant

Cosmetic Applications

Internal Lubricant

Rubber and Plastic Lubricant

Defoamers

SPECIAL FEATURES

Chemical Inertness

Non-Toxic

Versatile Release Agent

PROCESSING AND SAFETY GUIDELINES

Genesee Polymers' *GP-10(60000)* Silicone Fluid is nonhazardous, but in good manufacturing practice, care should be exercised in handling to prevent contact with skin or eyes. Consult Safety Data Sheet for additional details.

PACKAGING/HANDLING/STORAGE

GP-10(60000) Silicone Fluid is supplied in 5-gallon (40 lbs.) pails, 55-gallon (440 lbs.) drums and 330-gallon (2,640 lbs.) totes.



www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, express or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.