

# **GP-426 SILICONE FLUID**

Genesee Polymers' *GP-426 SILICONE FLUID* is a hydroxyl- terminated dimethyl polysiloxane with a nominal viscosity of 100 cSt at 25° C.

The hydroxyl groups of *GP-426* provide a reactive site, allowing it to become condensed with other hydroxyl groups or with Methyl Hydrogen Polysiloxanes in combination with heat or metal catalysts.

TYPICAL PROPERTIES	
Appearance	Clear, Colorless Liquid
Weight/Gallon	8.1 lbs
Specific Gravity	0.98
Refractive Index	1.4082
Viscosity, 25° C	100 cSt
% Silicone	100%

Product Code: C-4330 Version: 3.0 Revision Date: February 2, 2019

#### **APPLICATIONS**

Room Temperature Curing
Silicone Rubber Component

Hydrophobic Treatment of Powders and Pigments

Water Proofing Agent for Textiles, Paper and Leather

**Rubber Lubrication** 

**SPECIAL FEATURES** 

**High Purity** 

## PROCESSING AND SAFETY GUIDELINES

Genesee Polymers' *GP-426 SILICONE FLUID* may cause skin irritation. Consult Safety Data Sheet for additional safety information.

### PACKAGING/HANDLING/STORAGE

*GP-426 SILICONE FLUID* is supplied in 5-gallon (40 lbs.) pails, 55-gallon (440 lbs.) drums and 330-gallon (2640 lbs.) totes.



### www.gpcsilicones.com

This information is based on tests believed to be reliable. It is given only for your information and no warranty, express or implied, is made as we cannot guarantee the test conditions not under our direct control. This data is not intended as authorization or recommendation to practice a patented invention without knowledge or permission of the patent owner.